

## FTX Polyethylene insulated constant power cables




### Characteristics

- Hard-wearing, flexible and sealed.
- Can be cut to length on site.
- Extremely simple termination.
- Cold tail incorporated: no extra connection necessary.
- Available as 10 W/m.
- Power supply: 230 V.
- Copper braid and polyethylene outer sheath.

### Applications

The FTX cable is specially designed for protecting pipes carrying water against freezing. Its completely sealed, polyethylene outer sheath means that it can be placed inside the pipes.

To ensure that these heating elements enjoy a long service life, we recommend using a control device.



	FTX 10
Heating wire	Nickel-Copper or Nickel-Chrome
Dimensions	7 x 10 mm
Power	10 W/m
Conductor insulation	Silicon elastomer
Heating wire insulation	PVC 105°C
External insulation	Polyethylene
Permissible surface temperature	from - 30°C to + 80°C
Distance between 2 consecutive contact points	1 m

### Use

Consult the pages of the catalogue devoted to the corresponding general operating principles, general instructions for use and accessories.

#### FLEXELEC S.A.S

10, rue des frères Lumière  
 Z.A. du Bois Rond  
 69720 ST BONNET DE MURE - FRANCE  
 Tel: + 33 (0)4.72.48.30.90  
 Fax: + 33 (0)4.78.40.82.81  
 E-mail: flexelec@omerin.com

#### FLEXELEC Dept

OMERIN ASIA Pte Ltd  
 51 Goldhill Plaza #08-12/01  
 SINGAPORE 308900  
 Tel: + 65.6255.4778  
 Fax: + 65.6255.4779  
 E-mail: sales@omerin.com.sg

#### FLEXELEC (UK) Ltd

Unit 11 Kings Park Industrial Estate  
 Primrose Hill - KINGS LANGLEY  
 Hertfordshire - WD4 8ST - UK  
 Tel: + 44 (0) 1923.274477  
 Fax: + 44 (0) 1923.270264  
 E-mail: sales@omerin.co.uk

#### FLEXELEC Dept

OMERIN GmbH  
 Buchwiese 16  
 D-65510 IDSTEIN - GERMANY  
 Tel: + 49 (0) 6126.94.31-0  
 Fax: + 49 (0) 6126.83.99  
 E-mail: omeringmbh@omerin.com